

# CC-1000

## Mono amplifier

CC-1000 is a compact and powerful mono amplifier with a power of 1000 Watts RMS @ 1 ohm load. A popular and good power amplifier with high reliability. An amplifier for both amateurs and professionals.

- Built-in low-pass filter for subwoofers, variable between 35 and 250 Hz. Selectable 12 / 24 dB slope.
- Built-in protection circuits shut down the amplifier in the event of overloads
- BASS BOOST adjustable 0 +6 dB.
- Damping factor >154
- S/N ratio, A weighted: 92 dB
- Remote bass level control is included
- High level input with automatic start.
- -RMS output power @ 14,4 V



### Specifications

Number of channels Amplifier class Power output RMS, 1 ohm Power output RMS, 2 ohm Power output RMS, 4 ohm Signal to noise ratio, A-weighted Damping factor Frequency response Input impedance, low level Input sensitivity Input impedance, high level High level input with auto start Filter low pass variable Bass boost @ 60 Hz Subsonic filter Phase switch Remote sub level control Power consumption, idle Power consumption, max Fuse Dimensions HxWxD(mm / inch)

#### Power terminal size Speaker terminal size Weight

#### \_ \_ \_

2,9 kg

CC-1000 D 1000 W 700 W 440 W 92 dB 144 10 Hz - 500 Hz 22 kohm 1 - 4V 45 ohm Yes 35 - 250Hz, 12 or 24 dB slope 0 - +6 dB 30 Hz ON / OFF 0 / 180° Yes, with 5 meters cable 0,6 A 102 A Use external fuse 100 A 55 x 129 x 368 / 2,16 x 5,07 x 14,48" 2 AWG / 33 mm<sup>2</sup> 7 AWG / 10 mm<sup>2</sup>



DLS Sweden www.dls.se E-mail. info@dls.se